

VW197D

True-to-life Pictures Powered by LED

Mercury-free LED monitor delivers ultra-sharp images with great power savings.



True-to-life Pictures Powered by LED

Delivers Vibrant Images with Green Power Efficiency

With global resources becoming scarcer and the impact our demands have made on the planet becoming increasingly visible, green computing has become a critical issue in recent times. The VW197D LED monitor adopts LED backlight panel to delivers high contrast images and save over 40% power consumption with mercury free.



10,000,000:1 ASUS Smart Contrast Ratio

Dynamically enhances the display's contrast by adjusting the luminance of the backlight to achieve the darkest black and brightest white – delivering lifelike images.





Excellent Visual Performance with Exceptional Features

Aspect Control function allows users to select a preferred display mode among Full and 4:3 for true-to-life gaming or movie watching without any data loss or image distortion.



Splendid™ Video Intelligence Technology

The exclusive Splendid Video Intelligence Technology optimizes video performance and image fidelity by enhancing color, brightness, contrast, and sharpness. 6 preset video modes (Scenery, Theater, Game, Night View, sRGB and Standard) can be selected via a hotkey.



User-friendly Design

Convenient key controls for functional set-up in the multi-language OSD. VESA Wall Mount Standard (100 x 100 mm).

25° (forward 5°, backwards 20°) Tilting Angle.

KENSINGTON Security Lock.

Complete After-Sale Service

System warranty depends on different region Panel warranty depends on different region Free pick-up service (in specific countries)

Specifications

Panel Size : 18.5°(47.0cm) 16.9 Wide Screen True Resolution : 1368c788 Pixel Pitch : 0.3mm Brightness(Max) : 250 cd/m² ASUS Smart Contrast Ratio (ASCR) : 10000000:1 Viewing Angle (CR=10) : 170*(H)/160*(V) Response Time : 5ms Display Colors : 16.7M SPLENDID Video Intelligence Technology SPLENDID Video Preset Modes : 6 Modes Skin-Tone Selection : 3 Modes Color Temperature Selection : 4 Modes SPLENDID Video Preset Modes : 6 Modes Skin-Tone Selection : 3 Modes Color Temperature Selection : 4 Modes SPLENDID Video Preset Mode Selection Auto, Adjustment Brightness Adjustment Cortiant Adjustment Cortiant Adjustment Cortiant Adjustment Brightness Adjustment Cortiant Adjustment Cortia	оросиновного	
SPLENDID Video Preset Modes: 6 Modes Skin-Tone Selection: 3 Modes Color Temperature Selection: 4 Modes SPLENDID Video Preset Mode Selection Auto. Adjustment Brightness Adjustment Contrast Adjustment Contrast Adjustment Signal Input: D-Sub Signal Frequency Analog Signal Frequency: 30–80 kHz(H)/55–75 Hz(V) Power Consumption Power On < 23W Power Consumption Power Off Mode < 0.2W Chassis Colors: Black Titt: +20*-5° VESA Wall Mounting: 100x100mm Security Kensington lock Dimensions Phys. Dimension with Stand (WxHxD): 445.7x357.7x185mm Box Dimension (WxHxD): 507x322x150mm Weight Accessories VGA cable Power cord Quick start guide Support CD Warranty Card Energy Star 5.0, UL/cUL, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, , China Energy Label Level 1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307	Display	True Resolution: 1366x768 Pixel Pitch: 0.3mm Brightness(Max): 250 cd/m³ ASUS Smart Contrast Ratio (ASCR): 10000000:1 Viewing Angle (CR≧10): 170∜(H)/160∜(V) Response Time: 5ms
Auto. Adjustment Brightness Adjustment Contrast Adjustment (Contrast Adj	Video Feature	SPLENDID Video Preset Modes : 6 Modes Skin-Tone Selection : 3 Modes
Signal Frequency Analog Signal Frequency: 30-80 kHz(H)/55-75 Hz(V) Power Consumption Power ON < 23W Power Saving Mode < 0.2W Power Off Mode < 0.2W Chassis Colors: Black Tilt: +205° VESA Wall Mounting: 100x100mm Security Kensington lock Phys. Dimension with Stand (WxHxD): 445.7x357.7x185mm Box Dimension (WxHxD): 507x322x150mm Weight Net Weight (Esti.): 3.1kg Gross Weight (Esti.): 4.9kg VGA cable Power cord Quick start guide Support CD Warranty Card Energy Star 5.0, UL/cUL, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, , China Energy Label Level 1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307	Convenient Hotkey	Auto. Adjustment Brightness Adjustment
Power Consumption Power Saving Mode < 0.2W Power Off Mode < 0.2W Chassis Colors: Black Tilt: +20°5° VESA Wall Mounting: 100x100mm Security Kensington lock Dimensions Phys. Dimension with Stand (WxHxD): 445.7x357.7x185mm Box Dimension (WxHxD): 507x322x150mm Weight Net Weight (Esti.): 3.1kg Gross Weight (Esti.): 4.9kg VGA cable Power cord Quick start guide Support CD Warranty Card Energy Star 5.0, UL/cUL, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, , China Energy Label Level 1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307	I/O Ports	Signal Input : D-Sub
Power Consumption Power Saving Mode < 0.2W Power Off Mode < 0.2W Chassis Colors: Black Tilt: +20°5° VESA Wall Mounting: 100x100mm Security Kensington lock Dimensions Phys. Dimension with Stand (WxHxD): 445.7x357.7x185mm Box Dimension (WxHxD): 507x322x150mm Weight Net Weight (Esti.): 3.1kg Gross Weight (Esti.): 4.9kg VGA cable Power cord Quick start guide Support CD Warranty Card Energy Star 5.0, UL/cUL, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, , China Energy Label Level 1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307	Signal Frequency	Analog Signal Frequency: 30~80 kHz(H)/ 55~75 Hz(V)
Mechanical Design Tilt: +20°5° VESA Wall Mounting: 100x100mm Security Kensington lock Phys. Dimension with Stand (WxHxD): 445.7x357.7x185mm Box Dimension (WxHxD): 507x322x150mm Weight Net Weight (Esti.): 3.1kg Gross Weight (Esti.): 4.9kg VGA cable Power cord Quick start guide Support CD Warranty Card Energy Star 5.0, UL/cUL, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, , China Energy Label Level 1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307	Power Consumption	Power Saving Mode < 0.2W
Dimensions Phys. Dimension with Stand (WxHxD): 445.7x357.7x185mm Box Dimension (WxHxD): 507x322x150mm Weight Net Weight (Esti.): 3.1kg Gross Weight (Esti.): 4.9kg VGA cable Power cord Quick start guide Support CD Warranty Card Energy Star 5.0, UL/cUL, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, China Energy Label Level 1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307	Mechanical Design	Tilt: +20%-5°
Dimensions Box Dimension (WxHxD): 507x322x150mm Net Weight (Esti.): 3.1kg Gross Weight (Esti.): 4.9kg VGA cable Power cord Quick start guide Support CD Warranty Card Energy Star 5.0, UL/cUL, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, , China Energy Label Level 1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307	Security	Kensington lock
Weight Gross Weight (Esti.) :4.9kg VGA cable Power cord Quick start guide Support CD Warranty Card Energy Star 5.0, UL/cUL, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, , China Energy Label Level 1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307	Dimensions	•
Accessories Power cord Quick start guide Support CD Warranty Card Energy Star 5.0, UL/cUL, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, , China Energy Label Level 1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307	Weight	
1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307	Accessories	Power cord Quick start guide Support CD
	Regulation Approval	Energy Star 5.0, UL/cUL, CB, CE, FCC, CCC, BSMI, Gost-R, C-Tick, VCCI, PSB, J-MOSS, , China Energy Label Level 1, RoHS, WEEE, Windows Vista & Windows 7 WHQL, ISO 9241-307