



VGA2718

USB3.0 to VGA(D-sub)
Graphics Adapter



Introduction

SuperSpeed USB3.0 interface is the next revolution in I/O interconnect standards that will deliver the bandwidth and features required by PCs, consumer electronics and communications devices. With 10 times faster throughput than USB 2.0 standard, USB3.0 Graphic adapter enhances better VGA performance effect and reduce CPU loading substantially.

SUNIX VGA2718 Super-Speed USB3.0 Graphics Adapter provides a unique solution to add extra displays to a computer without using traditional graphics cards. Users can instantly mirror or extend a desktop onto another display via standard VGA(D-sub), such as LCD, CRT, projector and plasma displays. With USB interface plug-n-play and bus power feature, this product brings multi-monitor applications into the mainstream.

Features

- Add-on monitor, LCD or projector through USB3.0 or USB2.0 connectivity.
- Supports widescreen aspect ratio of 16:9 Full HD 1080P video streaming.
- High performance USB Graphics Engine supports resolutions up to 2048 x 1152 @ 32bit.
- Low power consumption via USB Bus power supply (without Heat Sink).
- Supports desktop display mirror, extend mode, multi screen mode and screen rotation mode
- Up to four USB3.0 graphic adapters to work simultaneously.
- Automatic recognition of monitor type, resolution, and features.
- Hot-swapping / Plug-n-Play of monitors without reconfiguration.
- Movement of windows on the desktop is smooth, with no trail or shuddering.
- Compatible with Windows power management hibernate and suspend modes.
- Specialized for office using, home entertainment, and video playing.
- Supports Microsoft Windows operation system.
- Certified by CE, FCC, and RoHS approval.

Ver1.0 JAN. 2011 Copyright 2010 by SUNIX Group all right reserved

Specification

Video Interface : VGA D-sub

Bus Interface: USB3.0 (Back compatible with USB2.0)

Connector:

D-sub 15pin Female Connector

Host upstream link:

USB3.0 Micro B Type Female Connector



(VGA)



(USB3.0 Micro B)



USB3.0 Host



USB2.0 Host

Memory: 16 MB x 16 DDR Synchronous DRAM (SDRAM)

Power Consumption: + 5VDC / 400mA over USB bus power

Support Mode: Extend mode, Mirror mode, Multi Screen mode, Screen Rotation mode

• **Extend Mode**



• **Mirror Mode**



• **Multi Screen Mode**



- This Mode needs more than one USB3.0 Graphics Adapters Using simultaneously. (Maximum 4 adapters connect to 4 displays)

• **Screen Rotation Mode**



Normal

90°

180°

270°

Ver1.0 JAN. 2011 Copyright 2010 by SUNIX Group all right reserved



SUNIX
www.sunix.com.tw

Plug into A Brand-new World

Resolutions :

640x480, 800x600, 1024x768, 1152x864, 1280x720,
1280x768, 1280x800, 1280x960, 1280x1024, 1360x768,
1400x1050, 1440x900, 1600x1200, 1680x1050,
1920x1080, 1920x1200, 2048x1152



Regulatory Approvals: FCC Part 15 Class B, CE (EN55022, EN61000, EN55024) ,
VCCI, C-Tick, BDMI, RoHS

O.S. Support : Windows 2000/XP/Vista/7 (X86/X64)



Environment : Operation temp. 10 °C ~ 40 °C (50-104°F)
Relative humidity: < 85% non-condensing
Storage temp. -10 °C ~ 85 °C (14~176°F)

Dimension: 56 (W) x 87(L) x 22(H) mm

Case Material: ABS

Weight: 50g±5g

USB Cable: USB3.0 A -Type Male to USB3.0 Micro B-Type Male

Ver1.0 JAN. 2011 Copyright 2010 by SUNIX Group all right reserved

SUNIX Taiwan Headquarters
<http://www.sunix.com.tw>
info@sunix.com.tw

SUNIX Vertriebs Gmbh
<http://www.sunix-europe.com>
info@sunix-gmbh.de

SUNIX do Brasil Ltda.
<http://www.sunix-brasil.com.br>
vendas@sunix-brasil.com.br

SUNIX USA Corp.
<http://www.sunix-usa.com>
info@sunix-usa.com




SUNIX
www.sunix.com.tw

Plug into A Brand-new World

Application





- Play game with strategy guide



- See and work with multiple documents at the same time – increase productivity



- Coding & testing



- Monitor stock & market news



Note: SUNIX recommends USB3.0 Graphics Adapter working over SuperSpeed USB3.0 connectivity to get best performance. But it's also backward compatible with HighSpeed USB2.0 environment.

Package Contents

1. USB Graphics Adapter
2. Driver CD ROM
3. Quick Installation Guide
4. USB3.0 cable 600mm (2.0 ft.)

Ver1.0 JAN. 2011 Copyright 2010 by SUNIX Group all right reserved

SUNIX Taiwan Headquarters
<http://www.sunix.com.tw>
info@sunix.com.tw

SUNIX Vertriebs Gmbh
<http://www.sunix-europe.com>
info@sunix-gmbh.de

SUNIX do Brasil Ltda.
<http://www.sunix-brasil.com.br>
vendas@sunix-brasil.com.br

SUNIX USA Corp.
<http://www.sunix-usa.com>
info@sunix-usa.com