

- >Green Ethernet technology link down power saving and link on various cable length power saving
- >IEEE 802.3x flow control provides reliable data transfer
- >Plastic case, desktop or wall-mounting design better for home and office use
- >Plug and play, no configuration required

Brief:

The netis ST3108G Gigabit Ethernet Switch provides 8 10/100/1000Mbps Auto-Negotiation RJ45 ports. All ports support Auto MDI/MDIX function, eliminating the need for crossover cables or Uplink ports. It provides high performance with minimum power consumption. It will cut power consumption when cable disconnected, then it wakes up and operates in normal mode when incoming signal detected, in which way that greatly reduces the power consumption.

www.netis-systems.com

8 Port Gigabit Ethernet Switch

ST3108G

Specification:

Hardware	
Interface	8 * 10/100/1000M RJ45 port, Auto-Negotiation, Auto MDI/MDIX
LED	PWR, 1-8 Link/Activity
Power Supply	DC 5V/2A(Output)
Dimensions (L x W x H)	183 x 125 x 31mm

Switching Features

Ī	Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE802.3ab 1000Base-T, IEEE 802.3x Flow Control
	Access Method	CSMA/CD
	Transmission Method	Store and Forward
	Switch Architecture	Non-blocking
	Data Transmission Rate	10/100/1000Mbps(Half-duplex) 20/200/2000Mbps(Full-duplex)
	MAC Address Table	8K, auto-learning & auto-aging

Others		
Certification	FCC, CE	
Environment	Operating Temperature: 0°C~40°C Storage Tem Operating Humidity: 10%~90% non-condensing Storage Hum	perature: -40°C~70°C nidity: 5%~90% non-condensing
Package	1 *ST3108G 1 *Quick Installation Guide 1 * P	ower Adapter

Topological Graph:

