

# MASTER VIEW

## KVM SWITCH CS-82A



### Features

- Supports Microsoft IntelliMouse and the Scrolling Wheel on Most Mice
- Keyboard and Mouse Emulation for Error Free PC Booting
- Easy to Install - No Software Required - Connecting Cables to the PCs Is All It Takes
- Easy to Operate - PC Selection Via Push Button Switches or Hotkeys - Auto Scan Function to Monitor PC Operation
- LED Display For Easy Status Monitoring
- Hot Pluggable
- Compatible With All Operating Platforms
- Caps Lock, Num Lock, and Scroll Lock States are Saved and Restored When Switching
- Superior Video Quality - Up To 1920 x 1440; DDC, DDC2, DDC2B
- Compact, Sturdy, Durable Metal Housing
- Efficient, Ergonomic Design; Logical Connector Layout
- Follows PC 99 Color Specifications
- Standard Cables for Computer Connections
- Saves Time, Space, Power, and Equipment Costs
- Non Powered Operation

### Specifications

Power Consumption		180 mW
Power Supply		Non powered
PC Connections		2
Port Selection		Push Button Switch; Hotkeys
LEDs	Selected	2
	On Line	2
Connectors	Keyboard	1 x 6 pin mini-DIN female (PS/2 style) - Console 2 x 6 pin mini-DIN female (PS/2 style) - CPU Ports
	Mouse	1 x 6 pin mini-DIN female (PS/2 style) - Console 2 x 6 pin mini-DIN female (PS/2 style) - CPU Ports
	Video	1 x HDB-15 female (std. VGA/SVGA) - Console 2 x HDB-15 male (std. VGA/SVGA) - CPU Ports
Resolution		Up to 1920 x 1440; DDC, DDC2, DDC2B
Scan Interval		5 Seconds
Conversion	Keyboard	PS/2
	Mouse	PS/2
Operating Temperature		5 ~ 40° C
Storage Temperature		-20 ~ 60° C
Humidity		0 ~ 80% RH, Noncondensing
Enclosure		Metal
Weight		420 g
Dimensions (L x W x H)		128 x 75 x 45 mm

**ATEN INTERNATIONAL CO., LTD.**

**TEL:886-2-8692-6789 FAX:886-2-8692-6767**

**CS-82A**