### **802.11g Wireless Print Server**

# TELEBRANE TO THE PROPERTY OF THE PROPERTY OF

#### PS-1206UWg / PWg

#### **Wireless Print Server**

1 Port USB 2.0 / Parallel Printer Server

#### **Supports Wired or Wireless Network**

The print server supports 10/100Mbps Wired and IEEE 802.11g/b wireless network. Users can share the printer and configure the print server either through a wired or wireless network.

# Easy Installation and Configuration (with Web-Based Configuration)

The print server's easy-to-use Windows installation wizard enables a quick installation

and setup of the print server. The print server can also be conveniently configured from any network client that supports web-browsing.

#### **Supports Peer-to-Peer and Server-Based Printing**

Supports both Peer-to-Peer and Server-based printing. LAN clients can connect directly with the print server to execute printing jobs (Peer-to-Peer printing); or clients can send print jobs first to a server (queuing jobs) and allow the server to connect with the print server to execute the printing jobs (Server-based printing).

#### **Provides Complete Printing Methods**

The print server provides LPR, IPP, SMB/TCP, Raw Printing and Unix Logical Printer printing methods. You can choose the best printing method according to your environment.

#### **Supports Major Operating Systems**

The print server is compatible with all major operating systems used today, for example Windows 95 / 98 / Me / NT / 2000 / XP, NetWare (3.x above), MAC OS and Unix/Linux environments.


#### **Fault-Tolerant Firmware Upgrades**

Users don't need to worry about errors occuring in the midst of an upgrade, thus preventing the print server from operating. The print server's fault-tolerant upgrade function allows for re-upgrades, should problems occur during the initial upgrade.





## **802.11g Wireless Print Server**



Taiwan / Headquarters Edimax Technology Co., LTD. TEL:886-2-7739-6888 FAX:886-2-7739-6887 sales@edimax.com.tw

China Beijing Edimax Science & Technology Co., LTD. TEL:8610-6213-9288 FAX:8610-6213-9231 sales@edimax.com.cn

U.S.A. Edimax Computer Company TEL:1-408-496-1105 FAX:1-408-980-1530 sales@edimax.com

Latin America TEL:1-786-845-8099 FAX:1-786-331-8490 sales\_latinamerica@edimax.com

Europe Edimax Technology Europe B.V. TEL:31-499-377344 FAX:31-499-372647 sales@edimax.nl

U.K. Edimax Technology (UK) Ltd. TEL:44-870-7740226 FAX:44-870-7740227 info@edimax.co.uk

F© (E

#### **Feature**

- Complies with IEEE 802.3, IEEE 802.3u Wired Ethernet and IEEE 802.11g/b (2.4GHz) Wireless LAN standards.
- Supports 10/100Mbps speed in Wired Network and up to 54Mbps data rate in Wireless Network.
- Provides one USB 2.0 or parallel port to connect to printer.
- Share printer with USB port to all PCs through a wired or wireless network.
- Supports TCP/IP, IPX/SPX, NetBEUI and AppleTalk network protocols.
- Supports LPR, IPP, SMB/TCP, Raw Printing and Unix Logical printing protocols.
- Supports Peer-to-Peer Printing (TCP/IP/IPX/NetBEUI/AppleTalk).
- Supports Server-based printing (Novell NetWare and Windows).
- Compatible with all major operating systems (Windows 95/98/Me/NT/2000/XP, NetWare (3.x above), MAC OS and Unix/Linux).
- Supports DHCP Server and Client protocol.
- Supports Web-based management, Windows Configuration Utility and SNMP Protocol.
- Provides easy-to-use installation, setup and diagnostic programs.
- Supports Fault-Tolerant Upgrade capability.

#### **Specification**

Model NO.	PS-1206UWg PS-1206PWg
CPU	RISC CPU
Flash	1MB NOR Flash
RAM	8MB SDRAM
Printer Port	USB 2.0 Parallel
LAN Port	10/100 Port x 1 (Auto-MDI/MDI-X)
Antenna	External 2dBi Dipole Antenna
Output Power	16dBm-18dBm
Power	5V DC, 2A Power Adaptor
Dimension	20(H) x 58(W) x 82(D) mm
Temperature	0~55°C
Humidity	10~90% (Non-Condensing)
Certification	FCC Class B, CE Mark

