



PS-1210Un

Wireless 802.11b/g/n USB 2.0 Print Server



Complies with wireless 802.11n standards

With the latest wireless 802.11n technology, the transmission data rate of PS-1210Un can be up to 150Mbps, it allows stronger wireless signal and guarantee high speed wireless connections compared to a standard wireless 802.11b/g network.

Broad Selection of Printing Methods

The PS-1210Un USB print server supports a wide selection of printing protocols such as LPR, IPP, SMB/TCP and RAW printing. They can also work with different network protocols like, TCP/IP, IPX/SPX, NetBEUI, and Apple Talk. This gives you a variety of printing methods to choose from based on your requirements.

Fault-Tolerant Firmware Upgrades

Now, users need not worry about errors occurring in the midst of an upgrade that may subsequently stop its operations. The PS-1210Un USB print server incorporates a fault-tolerant upgrade function that permits re-upgrading of the device should problems occur during the initial or previous upgrade session.

Secured Wireless Communication via 64/128-bit WEP, WPA & WPA2 Encryptions

The PS-1210Un USB print server supports 64/128-bit WEP data encryption to protect your wireless network from eavesdroppers. It also supports WEP, WPA and WPA2 robust encryptions in case intruder-free and safe transmission of data are your concerns

User-friendly Setup CD Wizard and Driver*

To facilitate connection to your printer, the PS-1210Un print server bundled with a user-friendly EZmax setup wizard CD. Its easy-to-use windows installation wizard simplifies and enhances the installation procedures, you can set it up within a minute. Once you have installed the print server, you can access and configure the print server via the web browser from any computers which is within the network.

FEATURES AND TECHNICAL SPECIFICATIONS

- Complies with wireless 802.11b/g/n standards
- Includes multilingual EZmax Setup Wizard
- Shares USB printer* among the network users
- Supports LPR, IPP and Raw printing protocols
- Supports SMB/TCP and Unix logical printing protocols
- Supports DHCP Client protocols
- Supports Web-based, Telnet management and Windows configuration Utility
- Supports Auto MDI/MDI-X and UPnP
- Compatible with most popular USB printers*

HARDWARE INTERFACE	MEMORY	POWER ADAPTER
<ul style="list-style-type: none"> • Wireless 802.11b/g /n • One USB port • One 10/100Mbps LAN port • Reset button • One 2dBi antenna 	<ul style="list-style-type: none"> • 2MB NOR Flash • 16MB SDRAM 	<ul style="list-style-type: none"> • 5VDC / 1A
INSTALLATION & MANAGEMENT KITS	SECURITY	LED
<ul style="list-style-type: none"> • Multilingual EZmax Setup Wizard • Admin Utility included • Web-based Management • Firmware upgrade utility 	<ul style="list-style-type: none"> • 64/128-bit WEP Encryption and WPA-PSK, WPA2-PSK security 	<ul style="list-style-type: none"> • WLAN • STATUS • LAN
SYSTEM REQUIREMENTS	OS	HUMIDITY & TEMPERATURE
<ul style="list-style-type: none"> • CPU: Pentium III 1G above or similar • Memory size: 256MB RAM • One CD-ROM drive • Hard Disk: Min. of 100MB disk space • USB Printer • Wireless 802.11b/g/n or Fast Ethernet network 	<ul style="list-style-type: none"> • Print Server : Windows 2000/XP/2003 /Vista/7, Mac 9.x above, Netware 3.x above and Linux/Unix 	<ul style="list-style-type: none"> • 10~90% (Non-condensing) • 0~40°C
DIMENSION	OUTPUT POWER	CERTIFICATIONS
<ul style="list-style-type: none"> • 60 (W) x 22 (H) x 81 (D) mm (without Antenna) 	<ul style="list-style-type: none"> • 16-18dBm 	<ul style="list-style-type: none"> • CE, FCC

TYPICAL SETUP DIAGRAM AND RELATED PRODUCTS



* Please check the list of compatible printers before you make your purchase.